

TASKI® swingo® 1255 B

Battery-powered 22-inch (55-cm) auto scrubber



Key Features

- ▶ Ideal size for best performance
- ▶ Excellent cleaning and drying results
- ▶ Simplicity and easy maintenance
- ▶ Durability and robustness

Ideal size for best performance

- ▶ The machine's patented CSD system always ensures the right amount of cleaning solution on the floor and leads to significant water savings. This feature, in combination with the 16-gallon (60-l) tank volume, increases productivity and reduces time-consuming tank filling stops during the cleaning operation. The dual-axle system ensures easy handling and allows comfortable use of the machine.

Excellent cleaning and drying results

- ▶ The machine's patented brush design follows the floor profile and delivers nearly even pressure allocation along the full working width. Two brushes are offset to the side, allowing superior cleaning along walls and under racks. This results in excellent soil removal and floor appearance. The patented V-shaped squeegee allows excellent water pick-up on all floor types, even on structured and grouted/tiled floors. Special squeegee blades and a direct suction line allow pick-up of small debris (e.g. cigarette butts) without clogging. Due to the proven three wheel concept, adjustments of the squeegee are no longer necessary.

Simple to use and easy maintenance

- ▶ All components needing frequent maintenance are color-coded in yellow and can be removed easily without tools. The dashboard is self-explanatory and displays all required information. Fewer parts to maintain and easy accessibility make the machine extremely service friendly.

Durability and robustness

- ▶ The use of high-tech material and long life components enhance the machine's uptime, while reducing service and repair costs to a minimum.

TASKI swingo 1255 B Specifications

TASKI swingo 1255 B Technical Data

Description		Description	
Practical performance	13,450 ft ² /h (1,250 m ² /h)	Dimensions (L x W x H)	56 x 23 x 46 inches (142 x 58 x 117 cm)
Working width	22 inch (55 cm)	Turning circle	3 feet (1 m)
Squeegee width	32 (80 cm)	Brush system	.75 x 11 inches (2 x 28 cm)
Solution tank (nominal)	16 gallon (60 l)	Brush pressure	106 lbs (48 kg)
Recovery tank (nominal)	16 gallon (60 l)	Cleaning speed	2.8 mph (4.5 km/h)
Nominal consumption	1,000 W	Power cord length of integrated battery charger	10 feet (3 m)
Rated voltage	24 V	Sound level	58 dB(A)
Battery capacity	100-140 Ah/C5	Protection class (BMS/non-BMS)	II/III
Battery run time (nominal)	up to 3 h	Approvals	CE/CB Test cert./cETL
Machine weight ready for use (power)	572 lbs (260 kg)		

TASKI swingo 1255 B

Model	SKU Number
TASKI swingo 1255 B traction drive and on board charger	7517715

Accessories/Additional Parts

Description	SKU Number
Drive discs 11 inch (28 cm)	7510.634
Hard nylon brush 11 inch (28 cm)	7510.631
Soft scrub brush 11 inch (28 cm)	7510.632
Pro-grit brush 11 inch (28 cm)	7510.633
AGM maintenance free batteries	8G31.1600

Additional Features

BMS (Battery Management System): Integrated in the machine, the battery charger prevents deep discharging of the battery and monitors the charging process.

TD (Traction Drive) The variable working speed up to 2.8 mph (4.5 km/h) and reverse speed up to 2 mph (3 km/h) guarantees ergonomic and effort-less utilization and increases performance compared to non-wheel drive models.

CSD (Cleaning Solution Dosing): The CSD system allows for a speed-dependent supply of cleaning solution. This feature ensures that the amount of solution dosed onto the floor is always constant—no matter how fast the machine is operating. The result? No puddles in curves and turns as well as a 30-50 percent saving in cleaning solution, leading to significantly increased productivity of the machine.