



Speed Scrub ec-H2O™

24, 28 & 32" disk specifications



Scrubbing System

Cleaning path (3 paths available)	24 in / 600 mm	28 in / 700 mm	32 in / 800 mm
Solution tank capacity	22.5 gal / 85 L		
Productivity (per hour)			
Theoretical max	26,400 ft² / 2,500 m²	30,800 ft² / 2,900 m²	35,200 ft² / 3,300 m²
Estimated actual* (conventional)	17,875 ft² / 1,660 m²	20,800 ft² / 1,900 m²	24,000 ft² / 2,200 m²
Estimated actual* (ec-H2O)	20,075 ft² / 1,900 m²	22,750 ft² / 2,100 m²	26,250 ft² / 2,400 m²
Solution flow rates: Standard			
Optional	0.15 gpm / 0.57 lpm		0.22 gpm / 0.83 lpm
Conventional Option	.22 gpm/ .83 lpm & .30 gpm/ 1.1 lpm		.33, .44 gpm/ 1.25, 1.66 lpm
Scrub motors	(2) 0.75 hp / 0.56 kW		
Scrub motor speed	220 rpm		
Brush / pad down pressure	Up to 120 lb / 54 kg		
Brush / pad driver quantity & size	(2) 12 in / 300 mm	(2) 14 in / 360 mm	(2) 16 in / 410 mm
Environmental Impact (Annual) ****			
Chemical use reduction	137 gal		
Packaging reduction	83 lbs		
Water use reduction	6143 gal		

Recovery System

Recovery tank capacity	27 gal / 102 L (Includes demisting chamber)
Vacuum fan	
Motor	0.85 hp / 0.640 kW
Stages	3-stage
Water lift	62 in / 1,570 mm

Propelling & Power System

Propel speed (variable to)	
Transport	2.7 mph / 4.3 km/h
Scrubbing	2.5 mph / 4.0 km/h
Batteries (24 V system, charger included)	
Standard / run time**	(4) 6V, 235 AH / Up to 5 hours
Optional Sealed (AGM) / Run time **	(4) 6V, 200 AH / Up to 4 hours
Gradeability (ramp climb)	
Scrubbing / transporting (full)	3.0° / 5.0°
Trailer ramps (empty)	11°
Speed control	Variable speed potentiometer

Dimensions / Weight / Sound level

Length	53 in / 1,350 mm	55.5 in / 1,410 mm	58 in / 1,470 mm
Width			
Body		23 in / 580 mm	
Scrub head	25.4 in / 640 mm	29 in / 740 mm	33 in / 840 mm
Squeegee	35.7 in / 910 mm	41.3 in / 1,050 mm	46.6 in / 1,180 mm
Height	44 in / 1,120 mm		
Net weight			
Less batteries	293 lb / 133 kg	320 lb / 145 kg	332 lb / 151 kg
With batteries (4) 6V 235 AH	569 lb / 258 kg	593 lb / 269 kg	606 lb / 275 kg
Minimum aisle turn:	53 in / 1,350 mm	59 in / 1,500 mm	64 in / 1,630 mm
Sound level*** (operator's ear)	67 dBA		

Warranty

3 years/2500 hrs on parts and labor (excluding batteries).
10 years on rotationally-molded polyethylene tanks.

* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

** Run times are based on Continuous Scrubbing Run Times.

*** Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA

**** Estimates based on requiring, at minimum, 1.5 tanks to clean the facility / area per day. 2 oz of chemical per gallon of water and scrubbing 5 times per week or 260 times per year.



Speed Scrub ec-H2O™

26 & 32" cylindrical specifications



Scrubbing System

	26 in / 650 mm	32 in / 800 mm
Cleaning path (2 paths available)		
Solution tank capacity	22.5 gal / 85 L	
Productivity (per hour)		
Theoretical max	28,600 ft ² / 2,700 m ²	35,200 ft ² / 3,300 m ²
Estimated actual* (conventional)	19,200 ft ² / 1,790 m ²	24,000 ft ² / 2,200 m ²
Estimated actual* (ec-H2O)	21,000 ft ² / 2,000 m ²	26,250 ft ² / 2,400 m ²
Solution flow rates: Standard	Standard: .22 gpm / .83 lpm	.33 gpm / 1.25 lpm
Optional	.33 gpm / 1.25 lpm	.44 gpm / 1.66 lpm
Conventional Option		
Scrub motors	(2) 0.63 hp / 0.47 kW	
Scrub motor speed	1500 rpm	
Brush / pad down pressure	Up to 120 lb / 54 kg	
Brush quantity & size	(2) 6 in / 150 mm	(2) 6 in / 150 mm

Environmental Impact (Annual)****

Chemical use reduction	162 gal	282 gal
Packaging reduction	99 lbs	172 lbs
Water use reduction	3,853 gal	10,116 gal

Recovery System

Recovery tank capacity	27 gal / 102 L (Includes demisting chamber)
Vacuum fan	
Motor	0.85 hp / 0.640 kW
Stages	3-stage
Water lift	62 in / 1,570 mm

Propelling & Power System

Propel speed (variable to)	
Transport	2.7 mph / 4.3 km/h
Scrubbing	2.5 mph / 4.0 km/h
Batteries (24 V system, charger included)	
Standard / run time**	(4) 6V, 235 AH / Up to 5 hours
Optional Sealed (AGM) / Run time **	(4) 6V, 200 AH / Up to 4 hours
Gradeability (ramp climb)	
Scrubbing / transporting (full)	3.0° / 5.0°
Trailer ramps (empty)	11°
Speed control	Variable speed potentiometer

Dimensions / Weight / Sound level

Length	55 in / 1,400 mm	
Width		
Body	23 in / 580 mm	
Scrub head	28 in / 710 mm	34 in / 860 mm
Squeegee	41.3 in / 1,050 mm	46.6 in / 1,180 mm
Height	44 in / 1,120 mm	
Net weight		
Less batteries	332 lb / 151 kg	342 lb / 155 kg
With batteries (4) 6V 235 AH	606 lb / 275 kg	615 lb / 279 kg
Minimum aisle turn:	62 in / 1,570 mm	64.5 in / 1,640 mm
Sound level*** (operator's ear)	68 dBA	

Warranty

3 years/2500 hrs on parts and labor (excluding batteries).
10 years on rotationally-molded polyethylene tanks.

* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

** Run times are based on Continuous Scrubbing Run Times.

*** Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA

**** Estimates based on requiring, at minimum, 1.5 tanks to clean the facility / area per day. 2 oz of chemical per gallon of water and scrubbing 5 times per week or 260 times per year.



Speed Scrub disk specifications



Scrubbing System			
Cleaning path (3 paths available)	24 in / 600 mm	28 in / 700 mm	32 in / 800 mm
Solution tank capacity	22.5 gal / 85 L		
Productivity (per hour)			
Theoretical max	26,400 ft² / 2,500 m²	30,800 ft² / 2,900 m²	35,200 ft² / 3,300 m²
Estimated actual* (conventional)	17,875 ft² / 1,660 m²	20,800 ft² / 1,900 m²	24,000 ft² / 2,200 m²
Estimated actual* (FaST®)	20,075 ft² / 1,900 m²	22,750 ft² / 2,100 m²	26,250 ft² / 2,400 m²
Solution flow rates			
Conventional (fully variable)		0 - 0.5 gpm / 0 - 1.89 lpm	
FaST®	0.15 gpm / 0.57 lpm	0.22 gpm / 0.83 lpm	
Scrub motors		(2) 0.75 hp / 0.56 kW	
Scrub motor speed		220 rpm	
Brush / pad down pressure		Up to 120 lb / 54 kg	
Brush / pad driver quantity & size	(2) 12 in / 300 mm	(2) 14 in / 360 mm	(2) 16 in / 410 mm
Recovery System			
Recovery tank capacity		27 gal / 102 L (Includes demisting chamber)	
Vacuum fan			
Motor		0.85 hp / 0.640 kW	
Stages		3-stage	
Water lift		62 in / 1,570 mm	
Propelling & Power System			
Propel speed (variable to)			
Transport		2.7 mph / 4.3 km/h	
Scrubbing		2.5 mph / 4.0 km/h	
Batteries (24 V system, charger included)			
Standard / run time**		(4) 6V, 235 AH / Up to 5 hours	
Optional Sealed (AGM) / run time**		(4) 6V, 200 AH / Up to 4 hours	
Gradeability (ramp climb)			
Scrubbing / transporting (full)		3.0° / 5.0°	
Trailer ramps (empty)		11°	
Speed control		Variable speed potentiometer	
Dimensions / Weight / Sound level			
Length	53 in / 1,350 mm	55.5 in / 1,410 mm	58 in / 1,470 mm
Width			
Body		23 in / 580 mm	
Scrub head	25.4 in / 640 mm	29 in / 740 mm	33 in / 840 mm
Squeegee	35.7 in / 910 mm	41.3 in / 1,050 mm	46.6 in / 1,180 mm
Height		44 in / 1,120 mm	
Net weight			
Less batteries	293 lb / 133 kg	320 lb / 145 kg	332 lb / 151 kg
With batteries (4) 6V 235 AH	569 lb / 258 kg	593 lb / 269 kg	606 lb / 275 kg
Minimum aisle turn:	53 in / 1,350 mm	59 in / 1,500 mm	64 in / 1,630 mm
Sound level*** (operator's ear)		67 dBA	
Warranty	3 years/2500 hrs on parts and labor (excluding batteries). 10 years on rotationally-molded polyethylene tanks.		

* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

** Run times are based on Continuous Scrubbing Run Times.

*** Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA



Speed Scrub cylindrical specifications



Scrubbing System		
Cleaning path (2 paths available)	26 in / 650 mm	32 in / 800 mm
Solution tank capacity	22.5 gal / 85 L	
Productivity (per hour)		
Theoretical max	28,600 ft² / 2,700 m²	35,200 ft² / 3,300 m²
Estimated actual* (conventional)	19,200 ft² / 1,790 m²	24,000 ft² / 2,200 m²
Estimated actual* (FaST®)	21,000 ft² / 2,000 m²	26,250 ft² / 2,400 m²
Solution flow rates		
Conventional (fully variable)	0 - 0.6 gpm / 0 – 2.27 lpm	
FaST®	0.15 gpm / 0.57 lpm	0.22 gpm / 0.83 lpm
Scrub motors	(2) 0.63 hp / 0.47 kW	
Scrub motor speed	1500 rpm	
Brush / pad down pressure	Up to 120 lb / 54 kg	
Brush quantity & size	(2) 6 in / 150 mm	(2) 6 in / 150 mm
Recovery System		
Recovery tank capacity	27 gal / 102 L (Includes demisting chamber)	
Vacuum fan		
Motor	0.85 hp / 0.640 kW	
Stages	3-stage	
Water lift	62 in / 1,570 mm	
Propelling & Power System		
Propel speed (variable to)		
Transport	2.7 mph / 4.3 km/h	
Scrubbing	2.5 mph / 4.0 km/h	
Batteries (24 V system, charger included)		
Standard / run time**	(4) 6V, 235 AH / Up to 5 hours	
Optional Sealed (AGM) / run time**	(4) 6V, 200 AH / Up to 4 hours	
Gradeability (ramp climb)		
Scrubbing / transporting (full)	3.0° / 5.0°	
Trailer ramps (empty)	11°	
Speed control	Variable speed potentiometer	
Dimensions / Weight / Sound level		
Length	55 in / 1,400 mm	
Width		
Body	23 in / 580 mm	
Scrub head	28 in / 710 mm	34 in / 860 mm
Squeegee	41.3 in / 1,050 mm	46.6 in / 1,180 mm
Height	44 in / 1,120 mm	
Net weight		
Less batteries	332 lb / 151 kg	342 lb / 155 kg
With batteries (4) 6V 235 AH	606 lb / 275 kg	615 lb / 279 kg
Minimum aisle turn:	62 in / 1,570 mm	64.5 in / 1,640 mm
Sound level*** (operator's ear)	68 dBA	
Warranty	3 years/2500 hrs on parts and labor (excluding batteries). 10 years on rotationally-molded polyethylene tanks.	

* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

** Run times are based on Continuous Scrubbing Run Times.

*** Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA