

JohnsonDiversey CH-9542 Münchwilen

08.02.2007





TASKI swingo 2500/3500 V2, Subassembly: Electrical parts

This Newsletter replaces the GTS Newsletter N 2004/11

Interfacebox 4123087 (19604-34)

Subject: **Display Freshwater**

Since the launch of the swingo 2500/3500 V 2 (Trio) the display for freshwater (LED) on the dashboard did not always function with the expected reliability (water hardness).

With the improved interfacebox the fresh water supply is now continuously monitored without having to adjust the corresponding parameters.

Functionality:

- The conductivity of the sensors are being checked when the machine is switched ON and the display shows the measured state:
 - o The "LED" lights if there is no water in the tube
 - o The "LED" goes off automatically as soon as the tube is filled with water
- If during working the fresh water tank is emptied a "beep" sounds and the LED switches on
- After refilling the tank with fresh water and switching on the pump, the LED automatically goes off after approx. 5 seconds

Service

- In this new interfacebox the varying water hardness has been taken into consideration
- The corresponding parameters (particularly for soft water) do not have to be adjusted anymore
- The spare part number remains the same
- There is a white sticker on the rear side for identification (no green point anymore)
- The velcro strips are already included

Production

TASKI swingo 2500/3500 with improved interfacebox

from machine-No. xxxxxxx006352