

M30 Daily Operational Checklist



Before cleaning with your machine there are a few pre-operational checks that need to be done to confirm your machine is ready to be used.

- ☐ Check the hydraulic fluid level.
 - ☐ Check the fuel level.
 - ☐ Check the condition of the main brushes.
Remove any string, banding, plastic wrap, or other debris wrapped around the brushes.
 - ☐ Check the main brush compartment right hand skirt and squeegee for damage and wear.
 - ☐ Check the optional side scrubbing brush or sweeping brush.
Remove any string, banding, plastic wrap, or other debris wrapped around the brush.
 - ☐ Check the condition of the side brush skirt or squeegee.
 - ☐ Confirm the radiator and hydraulic cooler fins are clean.
 - ☐ Check the engine coolant level.
 - ☐ Check the engine oil level.
 - ☐ Check the main brush compartment left hand skirt and squeegee for damage and wear.
 - ☐ Check the left solution tank cover seal for damage and wear.
 - ☐ Check the recovery tank cover seal for damage and wear.
 - ☐ Confirm the vacuum fan screen is clean.
 - ☐ Confirm the optional ES filter is clean.
 - ☐ Confirm the recovery tank is drained and clean.
 - ☐ Check the right solution tank cover seal for damage and wear.
 - ☐ Check the condition of the hopper dust filter and clean as required.
 - ☐ Check the hopper dust filter seals for damage and wear.
 - ☐ Check the vacuum hoses for debris or blockage.
 - ☐ Check the squeegees for damage and wear.
 - ☐ Check the optional FaST-PAK™ detergent concentrate level and replace as needed.
 - Ensure all conventional cleaning agents are drained and rinsed from the solution tank.
- NOTE: When FaST™ Scrubbing: Ensure the solution tank is filled with **clear cool water only**.
- ☐ Check the headlights, taillights and safety lights.
 - ☐ Check the steering and brakes for proper operation.
 - ☐ Check the service records to determine maintenance requirements.

List below any problems that occurred during operation.

OPERATOR _____ DATE _____

SUPERVISOR _____ DATE _____