
GTX Scrubber
Specifications



	Disc	Cylindrical
BODY CONSTRUCTION / DIMENSIONS		
Tank Material:	**Poly (3/8" (.95 cm) thick)**	**Poly (3/8" (.95 cm) thick)**
Chassis Construction:	**3/16" Steel (.3175 cm)**	**3/16" Steel (.3175 cm)**
Rear Wheels (diameter x width):	**(2) 12" x 5" (30 x 13 cm)**	**(2) 12" x 5" (30 x 13 cm)**
Size (L x W x H):	**54" x 26" x 55" (137/63/140 cm)**	**54" x 26" x 55" (137/63/140 cm)**
Weight:	**780 lbs. (354 kg)**	**780 lbs. (354 kg)**
Weight (w / 245 ah batteries):	**1,222 lbs. (554 kg)**	**1,222 lbs. (554 kg)**
BRUSH SYSTEM:		
Brush Size:	**26D: (2) 13" [(2) 33 cm]** **30D: (2) 15" [(2) 33.5 cm]** **34D: (2) 17" [(2) 43 cm]**	**24C: (2) 22" [(2) 55 cm]** **27C: (2) 25" [(2) 63.5 cm]** **30C: (2) 28" [(2) 71 cm]** **34C: (2) 32 [(2) 81 cm]**
Standard Brush Motor:	**(2) 0.75 hp (559 watts)/ 300 rpm**	**(2) 0.75 hp (559 watts)/ 750 rpm**
Optional Brush Motor:	**(2) 1.0 hp (746 watts)/ 350 rpm**	**NA**
Brush Speed:	**300 rpm**	**750 rpm**
EDGE Pad Size:	**28-EDGE (1) 28" x 14"** **32-EDGE (1) 32" x 14"**	**28-EDGE (1) 28" x 14"** **32-EDGE (1) 32" x 14"**
EDGE Pad Motor	**(1) 1.0 hp (780 watts) / 2000 or 2500 rpm**	**(1) 1.0 hp (780 watts) / 2000 or 2500 rpm**
Brush Down Pressure:	**0-250 lbs. (0 - 113 kg)**	**0-250 lbs. (0 - 113 kg)**
Actuator Rating	**500 lbs. (227 kg)**	**500 lbs. (227 kg)**
BATTERY SYSTEM:		
System Voltage:	**36 volts**	**36 volts**
Standard Battery Rating:	**245 AH**	**245 AH**
Optional Battery Rating:	**325 AH**	**325 AH**
Battery Run Time:	**Up to 7 hours**	**Up to 7 hours**
Charger (110-v / 60 Hz / 24-volt):	**36-v / 25 amp**	**36-v / 25 amp**
SOLUTION SYSTEM:		
Solution Tank Capacity:	**35 gal. (132 liters)**	**35 gal. (132 liters)**
Solution Flow Rate:	**0-1.5 gpm (0-6 lpm)**	**0-1.5 gpm (0-6 lpm)**
Solution Filter:	**Stainless Inline**	**Stainless Inline**
RECOVERY SYSTEM:		
Recovery Tank Capacity:	**41 gal. (155 liters)**	**41 gal. (155 liters)**
Vacuum Power:	**1.0 hp (746 watts)**	**1.0 hp (746 watts)**
Drain Hose:	**2.0" (5 cm) Diameter**	**2.0" (5 cm) Diameter**
Vacuum (lift / airflow):	**68" / 70 cfm (173 cm / 21 cmm)**	**68" / 70 cfm (173 cm / 21 cmm)**
Demisting Chamber:	**3 gal. (11 liters)**	**3 gal. (11 liters)**
DRIVE SYSTEM:		
Power:	**1.0 hp (746 watts), sealed**	**1.0 hp (746 watts), sealed**
Speed Control:	**Variable 0-320 ft. (0-97 m)**	**Variable 0-320 ft. (0-97 m)**
GENERAL:		
Minimum Aisle U-Turn	**56" (142 cm)**	**56" (142 cm)**
Sound Level:	**68 dBA**	**68 dBA**
Cleaning Width & Rate/Hour:	**26D: 28,600 sq. ft./hr. (8,717 m^2/hr.)** **30D: 33,000 sq. ft./hr. (10,058 m^2/hr.)** **34D: 37,400 sq. ft./hr. (11,399 m^2/hr.)**	**24C: 26,400 sq. ft./hr. (8,047 m^2/hr.)** **27C: 29,700 sq. ft./hr. (9,052 m^2/hr.)** **30C: 33,000 sq. ft.hr. (10,058 m^2/hr.)** **34C: 37,400 sq. ft./hr. (11,399 m^2/hr.)**

RPS CORPORATION
P.O. Box 368
Racine, WI 53401
Phone: (800)634-4060
Fax: (866)901-3335

© RPS Corporation 2014.
All Rights Reserved.
Since our policy is one of constant improvement,
all specifications are subject to change without notice.

AUTHORIZED DISTRIBUTOR