

THE KAIVAC® 1750

EQUIPMENT SPECIFICATIONS

■ DESCRIPTION

Water Tank	17 Gallons (64,4 l)
Spray Time	17 Minutes
Flow Rate	1 GPM (3,8 l/min)
Pressure	500 psi (34,5 bars)
Vac Tank	17 Gallons (64,4 l)
See-Through Vac Tank	Yes
Dump Hose	26" (66,04 cm) Long
Toilet Dumping	Yes
Vac Tank Cleanout	100%
Method of Dumping	Drain Hose
Vac Motor Lift	130" (330,2 cm)
Vac CFM	112 cfm (3172 l/min)
HEPA Blow Feature	300 mph (482,7 km/h)
DVD Player	Optional
HEPA Filtered Exhaust	Yes - Replaceable

■ CHEMICAL

Molded-In Chemical Holder	Gallon (2), Quart (1)
Chemical Switching	Dual/Quick Change
Safety Cap System	Yes
Metering Tip Settings	5 Settings

■ ELECTRICAL

Volts (U.S.)	110 Volt - 60 Hz
Volts (Universal)	100-240V; 50-60Hz
Amps Total	14.5 amp
GFCI	Yes

■ CORDS AND HOSES

Vac Hose	45 ft. (13,7 m)
Spray Line	45 ft. (13,7 m)
Quick-Connect Gun	Yes
Electric Cord	50 ft. (15 m)
Blow Hose	33 ft. (10 m)

■ BODY

Rotational Mold	Yes
Removable Engine Compartment	Yes - Black Box Technology
Weight	123 lb. (55,8 kg)
Size (H x L x W)	40" x 28" x 22" (101,6 x 81,3 x 55,9 cm)
Flat-free Non-marking Pneumatic Tires	(2) 8" (20,3 cm)
Casters	(2) 5" (12,7 cm), locking
Stair Climbing Wheels	Yes
Handle	Molded-In
Tray	Molded-In
Parking Brake	Yes

■ TOOLS INCLUDED

Vac Wand Aluminum	2-Piece
14 Inch Squeegee Head	Yes
Blow Nozzle	Yes
Training Materials	Video and Placard
KaiBrush	Yes
Window Squeegee	Yes
Metering Tip Kit	Yes
KaiDrain	Yes
15 Gallon Tote Bag	Yes

■ WARRANTY WITH KAIVAC CHEMICAL USAGE*

Body	10 Years
Parts	3 Years
Labor	1 Year

*International warranties may vary.



kaivac cleaning systems™
Complete Cleaning For Healthy Results™