

GENERAL INFORMATION

Machine Specifications

Solution Tank	4 gallons
Recovery Tank	4 gallons
Vacuum	Single 3-stage
CFM	100
Water Lift	130"
Pump PSI	120
Pump GPM	1.3
Heater	1,000W - 210° max.
Power Consumption	19 amps @ 115V 60Hz
Machine Weight	48 lbs.
Machine Dimensions	With handle: 33" x 12" x 36.5" Without handle: 18" x 12" x 28.5"
Power Cord	25' 12/3

230V Configuration Information

Model Number	8070-230
Power Consumption	9 amps @ 230V 60Hz/50Hz

FAQs

Q: What comes standard with the 8070?

A: The 8070 comes with 15' 1-1/4" Hose-n-Hose™ Vacuum/ Internal Solution Hose Combo (8501), a 4" Stainless Steel Upholstery Tool (8400), Cuff-Lynx™ H122, and a drain hose (A110).

Q: Does Mytee recommend a tool for the machine?

A: A variety of tools can be used with the unit, including our 8390 wand, 8700 crevice tool, 8400 upholstery tool, and 8400DX Mytee Dry™ upholstery tool.

Q: Where do I plug the machine in?

A: The 8070 requires a 20A grounded circuit. Please note: GFI outlets may trip before the breaker setting.

Q: What is the proper pre heat cycle for the 8070?

A: Turn pump switch to the on position and prime pump through the solution hose and the tool. Then turn the heater switch to the on position. Let the machine sit idle for 5-7 minutes. Spray tool until you feel the hot water from the jet.

Q: Are the pumps re-buildable for the 8070?

A: Yes, both the seals and the pistons have repair kits available. Please see the pump manual that shipped with your machine for the maintenance schedule.

Q: Is there anything I can do to increase the expected life of my machine?

A: Running the vacuum motors with the tank empty and lid off will allow excess moisture in the vacs to dry off. You should also run a System Maintainer through the system to keep the hoses, pump, and heater clean and free of debris.